

CANISTER LOAD CELLS COMPRESSION

REPLACEMENT REFERENCE CHARTS

To determine which TARE model to use for replacement, locate the manufacturer in the left column and to the right, the model being replaced. Read up for TARE's recommended replacement load cell type.

USE TARE CANNISTERS MODEL

| Model to be Replaced | TARE CC22 | TARE CP175 | TARE CP200 | TARE CP21 | TARE CP22 | TARE CP24 | TARE CP25 | TARE CP26 | TARE CP26S | TARE CP35 | TARE TC21 | TARE TC22 | TARE TC31 | TARE TC33 |
|----------------------|---------------------------------------|--|----------------------------|---|-------------------------|-----------|-----------|-----------|------------|-----------|--------------------|-----------------|--|-----------|
| BEOWULF | T3000C | 320 | 320S | 330 | 310 | 404 | | | | | | | 290 | 220 |
| BLH | | | | C2P1 | | | | | | | T2P1 | | | |
| CARDINAL | | 6950 | | | | | | HDD | SCA | | | | T3P1 C3P1 | |
| FAIRBANKS | | | | 3-38065-1 3-38065-2 3-38066-1 3-38066-2 3-43076-1 | | | | | | | | | 3-40766-13 3-40766-14 | |
| HOWE | | 20908120 20908117 20908119 20908121 | 244699-0002 244699-0004 | | | | | | | | | | | |
| HBM | | | | C-10 | | | | | | | | | | |
| NATIONAL | TC3000 | 3000CP | 300CSP | 3000 | | | | | | | 2000 | TS3000 | 2000 | 2000R |
| REVERE | | CP1 | CSP1 | 600641 | | | | | | | | | | USP1 |
| RTI | | C392 | C692 | | | | 92 | | | 92 | | | 63H 40 | |
| STREETER | | 3753070 3752030 3752040 3751940 | 3760270 3760903 | 2011612 3761281 | | | | | | | 2011716 2011717 | | 2011715 2011716 2011705 2011706 2011707 2011708 2011709 2011710 | |
| TOLEDO | Cap Check B10883600A B10887700A | | | 10049200A 10014900A 10011900A 10049300A | 04966 04967 04968 | | | | | | | 09622 Series | 10048 Series KN750668 | |
| TOROID | | 40 | | 38 | | 60CS | | | | | | | 35 | |

Use this chart as a guide only. Verify dimensions and performance specifications with Tare Inc.

CANISTER LOAD CELLS COMPRESSION

REVERE TRANSDUCER CP

A minimum size canister type compression load cell with high sensing capability. Hermetically sealed with built-in surge protection for use in compression applications; w/ standard 30 ft. cable.



SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 480 OHM
 FULL SCALE OUTPUT: 1.75 Mv/V NON-LINEARITY: + 0.03% FS
 MAX EXCITATION VOLTAGE: 20 VDC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-------------|------------|------------|-----------|
| RTI-CP-10K | 10,000 lb | \$ 1312.00 | \$ 984.00 |
| RTI-CP-25K | 25,000 lb | 1312.00 | 984.00 |
| RTI-CP-55K | 50,000 lb | 1312.00 | 984.00 |
| RTI-CP-1000 | 100,000 lb | 1465.00 | 1098.75 |
| RTI-CP-200K | 200,000 lb | 2095.00 | 1571.25 |
| RTI-CP-300K | 300,000 lb | 2305.00 | 1728.75 |
| RTI-CP-500K | 500,000 lb | 4480.00 | 3360.00 |

REVERE TRANSDUCER CSP

A hermetically sealed, high performance canister load cell with built-in surge protection. Ideally suited for high precision applications. NIST approved COC #88-082; w/ standard 30 ft. cable.



SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 450 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% FS
 MAX EXCITATION VOLTAGE: 20 VDC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|--------------|-------------|------------|-----------|
| RTI-CSP-10K | 10,000 lb* | \$ 1520.00 | \$1140.00 |
| RTI-CSP-25K | 25,000 lb | 1605.00 | 1203.75 |
| RTI-CSP-50K | 50,000 lb | 1605.00 | 1203.75 |
| RTI-CSP-100K | 100,000 lb | 1785.00 | 1338.75 |
| RTI-CSP-200K | 200,000 lb | 2395.00 | 1796.25 |
| RTI-CSP-300K | 300,000 lb* | 2495.00 | 1871.25 |
| RTI-CSP-500K | 500,000 lb* | 4685.00 | 3513.75 |

*Indicates Non NTEP

CANISTER LOAD CELLS TENSION/COMPRESSION

REVERE TRANSDUCER USP

A hermetically sealed high accuracy canister cell, Factory Mutual System Approved. This load cell can be used in both tension and compression applications; w/standard 30 ft. cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 3 Mv/V NON-LINEARITY: + 0.05% FS
 MAX EXCITATION VOLT: 15 VDC/AC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|--------------|------------|------------|------------|
| RTI-USP-100 | 100 lb | \$ 1665.00 | \$ 1248.75 |
| RTI-USP-250 | 250 lb | 1665.00 | 1248.75 |
| RTI-USP-500 | 500 lb | 1665.00 | 1248.75 |
| RTI-USP-1K | 1,000 lb | 1665.00 | 1248.75 |
| RTI-USP-2.5K | 2,500 lb | 1665.00 | 1248.75 |
| RTI-USP-5K | 5,000 lb | 1985.00 | 1488.75 |
| RTI-USP-10K | 10,000 lb | 1985.00 | 1488.75 |
| RTI-USP-25K | 25,000 lb | 2465.00 | 1848.75 |
| RTI-USP-50K | 50,000 lb | 3295.00 | 2471.25 |
| RTI-USP-100K | 100,000 lb | 8150.00 | 6112.75 |



REVERE TRANSDUCER 92/93

A high profile hermetically sealed multi-column Factory Mutual System Approved canister cell. Ideally suited for truck and track scales. Stainless Steel construction available; w/ standard 10 ft. cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% FS
 MAX EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|------------|------------|-----------|
| T-C92-5K | 5,000 lb | \$ 1185.00 | \$ 888.75 |
| T-C92-10K | 10,000 lb | 1185.00 | 888.75 |
| T-C93-20K | 20,000 lb | 1185.00 | 888.75 |
| T-C92-25K | 25,000 lb | 1185.00 | 888.75 |
| T-C92-50K | 50,000 lb | 1185.00 | 888.75 |
| T-C92-100K | 100,000 lb | 1185.00 | 888.75 |
| T-C93-150K | 150,000 lb | 2575.00 | 1931.25 |
| T-C93-200K | 200,000 lb | 2860.00 | 2145.00 |



CANISTER LOAD CELLS TENSION/COMPRESSION

REVERE TRANSDUCER MODEL 42/43

A medium/high capacity, hermetically sealed tension/compression cell, Factory Mutual System Approved; w/ standard 30 ft. cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% FS
 MAX EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|-----------|------------|-----------|
| T-T42U-5K | 5,000 lb | \$ 1145.00 | \$ 858.75 |
| T-T42U-10K | 10,000 lb | 1145.00 | 858.75 |
| T-T42U-20K | 20,000 lb | 1460.00 | 1095.00 |
| T-T42U-50K | 50,000 lb | 1880.00 | 1410.00 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

REVERE TRANSDUCER 62H

A load cell designed for both tension and compression loading. Hermetically sealed for use in hostile environments. Factory Mutual System Approved. Available in Stainless Steel; w/ standard 10 ft. cable.



SAFE OVERLOAD: 300% FS BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% FS
 MAX EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: 0-150° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|----------|------------|-----------|
| T-T62H-100 | 100 lb | \$ 1040.00 | \$ 780.00 |
| T-T62H-200 | 200 lb | 1040.00 | 780.00 |
| T-T62H-300 | 300 lb | 1040.00 | 780.00 |
| T-T62H-500 | 500 lb | 1050.00 | 787.50 |
| T-T62H-750 | 750 lb | 1050.00 | 787.50 |
| T-T62H-1K | 1,000 lb | 1050.00 | 787.50 |
| T-T62H-2K | 2,000 lb | 1070.00 | 802.50 |
| T-T62H-3K | 3,000 lb | 1070.00 | 802.50 |

TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE CP-22



An all Stainless Steel canister load cell. This low capacity compression TC cell is a direct replacement for Toledo's Universal Canisters Model Number A096227. The CP is a direct replacement for Toledo's Model Number 04966/67/68 and Beowulf 310 Series; w/standard 30' cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 240 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 20V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|-----------|------------|-----------|
| CP22-5K | 5,000 lb | \$ 1075.00 | \$ 806.25 |
| CP22-10K | 10,000 lb | 1075.00 | 806.25 |
| CP22-15K | 15,000 lb | 1175.00 | 881.25 |
| CP22-20K | 20,000 lb | 1175.00 | 881.25 |
| CP22-50K | 50,000 lb | 1175.00 | 881.25 |

TARE CC-22



An all Stainless Steel hermetically sealed canister load cell. This high capacity load cell is a direct replacement for Toledo's CAP-CHECK cells Models B10883600A, B10887700A and Beowulf's T3000C; w/standard 30' cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 775/850 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|------------|------------|-----------|
| CC22-50K | 50,000 lb | \$ 1100.00 | \$ 825.00 |
| CC22-100K | 100,000 lb | 1410.00 | 1057.50 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE CP21-10

An all Stainless Steel hermetically sealed canister load cell. This high capacity load cell is a direct replacement for FAIRBANKS MODEL NUMBER 3-43076-1 cells; w/standard 30' cable.

SAFE OVERLOAD: 150% FS BRIDGE RESISTANCE: 1000 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|-----------|------------|-----------|
| TCP210-50K | 50,000 lb | \$ 1050.00 | \$ 787.50 |



TARE CP-21

A compression type Stainless Steel load cell hermetically sealed, in cable or connector configuration. A direct replacement for: BLH C2P1, NATIONAL B-3000, TOROID 38, BEOWULF 330 & HBM C10. All physical & electrical specifications are identical; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|------------|------------|-----------|
| CP21-20K | 20,000 lb | \$ 1050.00 | \$ 787.50 |
| CP21-50K | 50,000 lb | 1050.00 | 787.50 |
| CP21-100K | 100,000 lb | 1050.00 | 787.50 |
| CP21-200K | 200,000 lb | 1425.00 | 1068.75 |



TARE CP175

A compression type Stainless Steel load cell hermetically sealed, NIST traceable, with a cable or connector fitting. Direct replacement for, RTI CP SERIES & RTI 392B, BEOWULF 320 & NATIONAL 3000-CP, Howe Richardson 20908120/717/119/121, Streeter 3753070/2030/2040/1940, Cardinal 6950, and Toroid 40. All physical and electrical specifications are identical; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 480 OHM
 FULL SCALE OUTPUT: 1.75 Mv/V NON-LINEARITY: + 0.10% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|------------|-----------|-----------|
| CP175-10K | 10,000 lb | \$ 765.00 | \$ 573.75 |
| CP175-25K | 25,000 lb | 765.00 | 573.75 |
| CP175-50K | 50,000 lb | 765.00 | 573.75 |
| CP175-100K | 100,000 lb | 915.00 | 686.25 |
| CP175-200K | 200,000 lb | 1545.00 | 1158.75 |
| CP175-300K | 300,000 lb | 1755.00 | 1316.25 |
| CP175-500K | 500,000 lb | 2980.00 | 2235.00 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE CP92/93

A compression type Stainless Steel load cell hermetically sealed, with cable or connector fitting. A direct replacement for RTI 92/93 SERIES load cells. All physical and electrical specifications are identical; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2/3 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|----------------|-----------------------|-----------|-----------|
| CP92/93-5K/10K | 5,000 lb Or 10,000 lb | \$ 825.00 | \$ 618.75 |
| CP92/93-20K | 20,000 lb | 825.00 | 618.75 |
| CP92/93-25K | 25,000 lb | 825.00 | 618.75 |
| CP92/93-50K | 50,000 lb | 825.00 | 618.75 |
| CP92/93-100K | 100,000 lb | 905.00 | 678.75 |
| CP92/93-150K | 150,000 lb | 1980.00 | 1485.00 |
| CP92/93-200K | 200,000 lb | 2215.00 | 1661.25 |

TARE CP-26S

A compression type Stainless Steel load cell hermetically sealed. This cell is a direct replacement for CARDINAL HDD/SCA. All physical and electrical specifications are identical; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 1050 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-------------|----------------------|-----------|-----------|
| CP26S-50K | 50,000 lb (Non-NTEP) | \$ 930.00 | \$ 697.50 |
| CP26S-50K-N | 50,000 lb (NTEP) | 1035.00 | 776.25 |

TARE CP200

A Stainless Steel compression type load cell that is hermetically sealed for use in hostile environments. A direct replacement for RTI CSP1, RTI 692-B, BEOWULF 320S, Howe Richardson 244699-0002/244699-0004, Streeter 3760207/3760903 and NATIONAL-3000CSP. All physical and electrical specifications are identical; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 480 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|------------|------------|-----------|-----------|
| CP200-10K | 10,000 lb | \$ 765.00 | \$ 573.75 |
| CP200-25K | 25,000 lb | 765.00 | 573.75 |
| CP200-50K | 50,000 lb | 765.00 | 573.75 |
| CP200-100K | 100,000 lb | 915.00 | 686.25 |
| CP200-200K | 200,000 lb | 1545.00 | 1158.75 |
| CP200-300K | 300,000 lb | 1755.00 | 1316.25 |
| CP200-500K | 500,000 lb | 2980.00 | 2235.00 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE TC-21

A Stainless Steel tension/compression hermetically sealed canister load cell. A direct replacement for BLH T2P1, NATIONAL'S 2000 and STRETTER'S, # 2011717-716, RTI 62/63 UP TO 3K, RTI 42 UP TO 100K, load cells; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|------------|-----------|-----------|
| TC21-500 | 500 lb | \$ 700.00 | \$ 525.00 |
| TC21-1K | 1000 lb | 700.00 | 525.00 |
| TC21-2K | 2000 lb | 700.00 | 525.00 |
| TC21-3K | 3000 lb | 700.00 | 525.00 |
| TC21-5K | 5000 lb | 787.50 | 590.60 |
| TC21-10K | 10000 lb | 787.50 | 590.60 |
| TC21-20K | 20000 lb | 1050.00 | 787.50 |
| TC21-25K | 25,000 lb | 1050.00 | 787.50 |
| TC21-30K | 30,000 lb | 1050.00 | 787.50 |
| TC21-50K | 50,000 lb | 1400.00 | 1050.00 |
| TC21-100K | 100,000 lb | 1400.00 | 1050.00 |



TARE TC-33

A Stainless Steel tension/compression hermetically sealed canister load cell. A direct replacement for RTI USP1, National 2000R, Beowolf 220, load cells; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 3 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|-----------|-----------|-----------|
| TC33-250 | 250 lb | \$ 700.00 | \$ 525.00 |
| TC33-500 | 500 lb | 700.00 | 525.00 |
| TC33-1K | 1,000 lb | 700.00 | 525.00 |
| TC33-2.5K | 2,500 lb | 700.00 | 525.00 |
| TC33-5K | 5,000 lb | 787.50 | 590.60 |
| TC33-10K | 10,000 lb | 787.50 | 590.60 |
| TC33-25K | 25,000 lb | 1050.00 | 787.50 |
| TC33-50K | 50,000 lb | 1400.00 | 1050.00 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE TC62

This Stainless Steel tension/compression hermetically sealed canister load cell is designed for use in hostile environments. A direct replacement for RTI 62H load cells; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|----------|-----------|-----------|
| TC62-200 | 200 lb | \$ 700.00 | \$ 525.00 |
| TC62-300 | 300 lb | 700.00 | 525.00 |
| TC62-500 | 500 lb | 700.00 | 525.00 |
| TC62-750 | 750 lb | 700.00 | 525.00 |
| TC62-1K | 1,000 lb | 700.00 | 525.00 |
| TC62-2K | 2,000 lb | 725.00 | 543.75 |
| TC63-3K | 3,000 lb | 725.00 | 543.75 |

TARE TC63

This Stainless Steel tension/compression hermetically sealed canister load cell is designed for use in hostile environments. A direct replacement for RTI 63H up to 3K and RTI Model 42/43 up to 100K load cells; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 3 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|----------|-----------|-----------|
| TC63-200 | 200 lb | \$ 700.00 | \$ 525.00 |
| TC63-300 | 300 lb | 700.00 | 525.00 |
| TC63-500 | 500 lb | 700.00 | 525.00 |
| TC63-750 | 750 lb | 700.00 | 525.00 |
| TC63-1K | 1,000 lb | 700.00 | 525.00 |
| TC63-2K | 2,000 lb | 725.00 | 543.75 |
| TC63-3K | 3,000 lb | 725.00 | 543.75 |

TARE TC-42

A Stainless Steel tension/compression hermetically sealed canister load cell. A direct replacement for RTI 43, load cells; w/standard 30' cable.



SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|-----------|-----------|-----------|
| TC42-5K | 5,000 lb | \$ 787.50 | \$ 590.60 |
| TC42-10K | 10,000 lb | 787.50 | 590.60 |
| TC42-20K | 20,000 lb | 1050.00 | 787.50 |
| TC42-50K | 50,000 lb | 1400.00 | 1050.00 |



TARE INC. REPLACEMENT CANISTER LOAD CELLS

TARE TC-42/43

A Stainless Steel tension/compression hermetically sealed canister load cell. A direct replacement for RTI 43, load cells; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 3 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLTAGE: 15 VDC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|-----------|-----------|-----------|
| TC43-5K | 5,000 lb | \$ 787.50 | \$ 590.60 |
| TC43-10K | 10,000 lb | 787.50 | 590.60 |
| TC43-20K | 20,000 lb | 1050.00 | 787.50 |
| TC43-50K | 50,000 lb | 1400.00 | 1050.00 |



TARE TC-31

A tension/compression Stainless Steel canister cell hermetically sealed. A direct replacement for the following cells: BLH T3P1 & C3P1, BEOWULF 230 & TOROID 35; w/standard 30' cable.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 3 Mv/V NON-LINEARITY: + 0.05% RO
 MAX. EXCITATION VOLT: 15V AC/DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|-----------|------------|-----------|----------|
| TC31-500 | 500 lb | \$ 700.00 | \$525.00 |
| TC31-1K | 1,000 lb | 700.00 | 525.00 |
| TC31-2K | 2,000 lb | 700.00 | 525.00 |
| TC31-3K | 3,000 lb | 700.00 | 525.00 |
| TC31-5K | 5,000 lb | 787.50 | 590.60 |
| TC31-10K | 10,000 lb | 787.50 | 590.60 |
| TC31-20K | 20,000 lb | 1050.00 | 787.50 |
| TC31-25K | 25,000 lb | 1050.00 | 787.50 |
| TC31-30K | 30,000 lb | 1050.00 | 787.50 |
| TC31-50K | 50,000 lb | 1400.00 | 1050.00 |
| TC31-100K | 100,000 lb | 1400.00 | 1050.00 |



TARE WT-1210

A precision compression canister load cell in 2K and 5K capacity. A direct replacement for the Winslow/Emery 1211 Totalizer load cell system. Supplied with Bendix PCO4E-10-6P connector, standardized output, and mounting plate; w/standard 10' cable and 1/4" NPT conduit connector upon request.

SAFE OVERLOAD: 150% BRIDGE RESISTANCE: 350 OHM
 FULL SCALE OUTPUT: 2&4 Mv/V NON-LINEARITY: + 0.02% RO
 MAX. EXCITATION VOLT: 25V DC COMPENSATED TEMP RANGE: +14°F to 104° F

| ORDER NO. | CAPACITY | PRICE | NET |
|--------------|------------|-----------|-----------|
| WT1210-2K | 2,000 lb | \$ 966.00 | \$ 690.00 |
| WT1210-5K | 5,000 lb | 600.00 | 450.00 |
| WT1210-10K | 10,000 lb | 600.00 | 450.00 |
| WT1210-25K | 25,000 lb | 775.00 | 581.25 |
| WT-1210-50K | 50,000 lb | 775.00 | 581.25 |
| WT-1210-100K | 100,000 lb | 920.00 | 690.00 |

