

REMOTE DISPLAYS

TARE REMOTE DISPLAY

These bright LED/LCD remote displays in fiberglass enclosure are built to work with any indicator that has an RS232 serial output option. Selectable baud rates 300, 1200, 2400, 4800, 9600. Data plug connector type DB9. Power requirement 120 VAC 50/60 Hz, 18 watts. Size 9.5" W x 8.25" H x 5.0" D. Ship weight 6 lbs. Warranty 1 year.

| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|-----------|--|-----------|-----------|
| B003 | RDS900-F | .8" High LED Display in Fiberglass Enclosure | \$ 745.00 | \$ 565.00 |
| B004 | RDS1000-F | 1" High LCD Display in Fiberglass Enclosure | 764.00 | 500.00 |



REMOTE "INTELLIGENT" DISPLAY

This series of intelligent scoreboards utilize microprocessor- based circuitry that is highly reliable. Upon initial installation, the built-in button enables the "Learn Mode", the scoreboard then monitors the input for valid data from the digital indicator. Once a valid string is recognized and displayed, scroll the displayed digits to the left or right until the correct digits are in view. The configuration is then stored in Non-Volatile memory and installation is complete. The highly reliable light fluorescent digits are easy to read and have a 150 degree viewing angle. Sizes range from 1.5" thru 6" and can be read from distances in excess of 200 feet. The scoreboards are housed in rugged NEMA 4X watertight steel enclosures and can withstand operating temperatures ranging from -40 degrees C to +75 degrees C. Features include built-in RS232 or 20 mA current loop. Power requirement 120 VAC 50/60 Hz. Size: see below on each model. Warranty 1 year.

| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|----------|--|-----------|-----------|
| B005 | IR-1.5 | 1.5" High Display (12" L x 6.5" H x 4" D x 13 lbs) | \$1176.00 | \$ 750.00 |
| B006 | IR-4 | 4" High Display (24" L x 9.5" H x 5" D x 29 lbs) | 1715.00 | 1115.00 |
| B007 | IR-6 | 6" High Display 36" L x 13.25 H x 5" D x 49 lbs) | 2150.00 | 1398.00 |



REMOTE DISPLAY BCD

This series receives BCD and displays weight data via 6 digit, 0.8" high intensity LED display. Continuous or on-demand display selectable update. Fiberglass NEMA 4 enclosure or boards only, see below. Warranty 1 year.

| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|------------|-----------------------------|-----------|-----------|
| B060 | RDS-BCD F | Nema 4 Fiberglass Enclosure | \$ 445.00 | \$ 312.00 |
| B060-1 | RDS-BCD BO | Boards only | 250.00 | 180.00 |



REMOTE DISPLAY LED SERIAL

This remote display receives ASCII and scale indicator serial data signals (20 mA current loop), and displays weight data on a 0.8" LED display. Sums up to three identical scale indicators. Status indicators are provided for lb, kg, gross, net, zero. Supports 4 of the most popular serial scale formats. Interfaces to other indicators or instruments are available at a nominal charge, contact factory. Available in fiberglass NEMA enclosure or boards only. Warranty 1 year.



| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|-----------|---|-----------|-----------|
| B070 | RDS800-F | Nema 4 Fiberglass Enclosure | \$ 843.00 | \$ 590.00 |
| B072 | RDS800-FS | Nema 4 Fiberglass Enclosure (Sum & Re-transmit) | 1053.00 | 737.00 |
| B070-1 | RDS800-BO | Boards only | 650.00 | 488.00 |

REMOTE DISPLAY 2" LCD

This remote display features six 2" LCD digits with 3 annunciators. Receives RS-232 and serial communications. Optional direct fiber-optic drive. Fluorescent backlight. Four indicators for LB, KG, GROSS, AND NET. NEMA 4 Fiberglass enclosure latched by two stainless steel butterfly latches, suitable for outdoor exposure. Overall enclosure size: 19-1/4" x 13-1/4" x 6.88", optional stainless steel mounting bracket or non-metal feet available. Standard mounting centers: 11.02" x 18.38". Warranty 1 year.



| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|----------|--|------------|-----------|
| B095 | RD2-F | LCD Display With Nema 4 Fiberglass Enclosure | \$ 1108.00 | \$ 749.00 |
| B095-2 | RD2-FRP | Fiberglass Mounting Feet | 60.00 | 42.25 |
| B095-3 | RDS-0 | Optional Pushbutton Switch | 56.00 | 40.00 |

REMOTE DISPLAY 3" LCD

This remote display features six 3" LCD digits with 4 annunciators. Receives 20 mA current loop, (active or passive), RS-232/422 or TTL communications. Optional direct fiber-optic drive. Fluorescent backlight. Five indicators for ZERO, GROSS/NET, TARE, UNITS, and PRINT. NEMA 4 Fiberglass enclosure latched by two stainless steel butterfly latches, suitable for outdoor exposure. Overall enclosure size: 19-1/4" x 13-1/4" x 6-7/8", optional stainless steel mounting bracket or non-metal feet available. Standard mounting centers: 11.02" x 18.38". Warranty 1 year.



| ORDER NO. | PART NO. | DESCRIPTION | PRICE | NET |
|-----------|----------|--|------------|-----------|
| B096 | RDS3-F | LCD Display With Nema 4 Fiberglass Enclosure | \$ 1299.00 | \$ 975.00 |
| B096-2 | RDS3-M | Fiberglass Mounting Feet | 60.00 | 42.25 |
| B096-3 | RDS-0 | Optional Pushbutton Switch and Boot | 60.00 | 42.25 |